



## **Agmark Bulk Tank Adapter Kit**

We supply this bulk tank adapter kit to allow the user to unload a bulk tank under pressure.

Included in the kit are (see picture on opposite side):

- 1) 3" elbow with a camlock fitting at the discharge end,
- 2) a wrench for tightening the elbow to the tank discharge port; do not always expect to be able to tighten the elbow sufficiently to prevent slight leakage; a coating of silicone grease on the metal-to-metal seal can work, but you may need a pail to collect drippings,
- 3) an adapter that reduces the 3" camlock on the elbow to a 3/4" camlock compatible with the hoses supplied in our rental injection systems; the adapter includes a pressure gauge to allow monitoring of the gas pressure used to unload the tank and a shut-off valve, and
- 4) a gas line valve with a 1/4" automotive coupler plug for charging the tank with pressurized gas to increase the discharge rate of Newman Zone®. Note that the bottom seal of the ball valve and the ball itself are loose from the valve body. Please insure that these parts are not lost.

DO NOT ATTACH THE BULK TANK DIRECTLY TO OUR INJECTION EQUIPMENT. The lower end of the Dosmatic proportional feeder must operate at LESS THAN atmospheric pressure. Under the head of the tank, the amendment will siphon through the feeder at a rate much higher than desired and may cause the feeder to stop altogether.

All parts of the kit are property of RNAS Remediation Products and should not be given to the Agmark driver for return. Please return the kit to:

RNAS Remediation Products  
6712 West River Road  
Brooklyn Center, MN 55430

